

KLIS IPCAM-5M-SD

5-Megapixel CMOS-based Network Camera

- Up to 5 megapixel resolution, 8 fps@2560x1920
- Output real time video at FULL HD 1080P, UXGA(1600x1200) • H.264 video compression
- Progressive scan CMOS
- SD/SDHC card local storage
- ICR filter auto switch
- Two-way audio
- ePTZ



Specifications

<i>Modello</i>		<i>IPCAM-5M-SD</i>
Camera	Image sensor	1/2.5 inch Progressive Scan CMOS
	Effective pixels	2560 x 1920
	Min Illumination	Color: 0.5 Lux @ F1.2 B/W:0.1 Lux @ F1.2; Sens-up: 0.008 Lux @ F1.2
	Electronic Shutter	1s ~ 1/20,000s
	Day & Night	IR cut filter with auto switch
	Lens Mount	C/CS mount
	Auto IRIS	DC Drive
	Video Parameter	Saturation/Brightness/Contrast/Tue adjustable through client software or web browser
Compression Standard	Video Compression	H.264/MPEG-4/Mjpeg
	Video Bit Rate	32 K~16Mbps
	Audio Compression	OggVorbis
Image	Max. Image Resolution	2560 x 1920
	Frame Rate	8fps @ 2560x1920, 20fps @ 2048x1536, 30fps @ 1600x1200,30fps @ FULL HD1080P, 30fps @ HD720P
Functions	e-PTZ	Yes
	Storage	Support SD/SDHC, NAS, ISCSI
	Intelligent Alarm	Motion Detection, Video Tampering, Video Loss, Network Broken, IP address conflict, Storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTCP, PPPoE, FTP, SMTP, NTP, SNMP, HTTPS, SIP, 802.1x, IPV6
	Basic	Initial Set button, Anti-flicker, Dual Stream, Heartbeat, Password Protection, watermark
Interface	Audio Input	1 channel 3.5mm audio interface (2.0 ~ 2.4Vp-p, 1k)
	Audio Output	1 channel 3.5mm audio interface (Line level, 600)
	Communication	1 RJ45 10M / 100M self-adaptive Ethernet port and 1 RS-485 interface
	Alarm Input	4 channel
	Alarm Output	3 channel
	Video Output	1Vp-p Composite Output (75/BNC)
General	Power Supply	DC12V±10% / PoE (AC24V optional)
	Power Consumption	12W MAX
	Working Temperature	-10°C ~ 60°C
	Working Humidity	90% or less
	Dimensions	68 x 77.4 x 154.5
	Weight	1000g

La pubblicazione di questo documento da parte di GSGInternational srl. non implica l'accuratezza o la completezza del suo contenuto, che potrà essere modificato in qualunque momento senza preavviso.

Compliance FCC, CE ISO 9001:2000
Garanzia di 2 anni

